# 0 603 3A9 322 – PBH 2000 RE

Material number	0 603 3A9 322
EAN	3165140853545
Auxiliary handle 2 602 025 102	$\checkmark$
Bosch SDS adapter chuck 2 609 255 708	$\checkmark$
<b>Depth stop</b> 2 603 001 019	$\checkmark$






## 0 603 3A9 322 - PBH 2000 SRE

## **Technical data**

#### Technical data

Power input	550 W
Power output	300 W
No-load speed	0 – 2,000 rpm
Impact rate	0 – 5,100 bpm
Single impact force (EPTA)	1,7 J
Bosch hammer mechanism	pneumatic
Machine weight	2,2 kg
Packaging dimensions (width)	370 mm
Packaging dimensions (length)	380 mm
Packaging dimensions (height)	110 mm
Packaging dimensions (width x length x height)	370 x 380 x 110 mm
Weight including packaging	4,66 kg



## **Drilling range**

Max. drilling diameter in concrete	22 mm
Max. drilling diameter in steel	13 mm
Max. drilling diameter in wood	30 mm

### Functions

Pneumatic hammer mechanism	1
Rotation Stop	$\checkmark$
Bosch Electronic	$\checkmark$
Chisel function	$\checkmark$
Right-hand/left-hand rotation	√
Bosch SDS plus	$\checkmark$
Softgrip	1
Application: screwdriving / drill. / hammer drill.	1

#### Linked digital objects

Feature objects
-----------------

2683795 2683794 2683796 2683797 2683798

#### Noise/vibration information

Sound pressure level	93.5 dB(A)
Sound power level	104.5 dB(A)
Uncertainty K	3 dB



## **Sales information**

#### Positioning

High-powered and compact for drilling, hammering, and chiselling

#### User benefit

- 550 W motor and pneumatic hammer mechanism with 1.7 j for any application
- SDS plus chuck for tool-less drill change and SDS adapter drill chuck for round drill bits
- Hammering and chiselling in concrete and masonry; drilling in tile, wood, and metal
- Chisel function with Vario Lock provides various selectable chisel positions
- Lightweight (2.2 kg; drills up to 20/30/13 mm diameter in concrete/wood/metal